

Product	EcoBurner Portable Burner P/N 8999
Fuel	LPG - Butane/Propane Mixture
Power Output*	MAX setting = Equivalent to traditional Ethanol/Methanol based Gel chafing fuel. Reduced setting = Equivalent to traditional DEG based wick chafing fuel.
Burn Time*	5 hrs on MAX setting. 7.5 hrs on reduced setting.
Fuel Fill Time*	40 seconds from empty.
Fuel Fill Weight*	90 g (3.17 oz)
EcoBurner Empty Weight*	345 g (12.17 oz)
Safety Features	Patented tip-over safety valve – shuts off fuel supply if the EcoBurner becomes inverted. Patent pending over-temperature valve – shuts off fuel supply if the EcoBurner vessel over-heats.
Certification	Complies with the European Gas Appliances Directive and is CE marked. ETL Listed Mark certifying product compliance to ANSI American safety standards and CSA Canadian safety standards.
Packaging	18 EcoBurners per outer pack. Pack Weight 7.6 kg (16.75 Lb) 72 packs per pallet – 1296 EcoBurners per pallet Pallet Weight 570 kg (1257 Lb) Harmonised Tariff Code 7321119000 Country of origin: Ireland
Materials	EcoBurner outer body: 304 grade stainless steel (also known as 18/10 grade), CW614N grade brass. EcoBurner outer body can be cleaned with industry standard detergents and degreasers but the coating on the EcoBurner head is catalytic and should be protected from any abrasive chemical cleaning.
*Figures are approximate. All Dimensions and Weights are approximate with 5% tolerance. Dimensions are in mm [inch]. Weights are in kg (Lb).	

