

Product Specification

Model		AT9G6B0-2					
Exterior Dimension (mm)		1200*900*1140					
Packing Dimension (mm)		1275*1015*1220					
Net Weight (kg)							
Gross Weight (kg)							
Burner		G20	G25.3	G30/G31			
	Power (kW)	Quantity (pc)	20mbar	25mbar	30mbar	37mbar	50mbar
		Nozzle No					
Hot plates	3.5	0	/	/	/	/	/
	7	0	/	/	/	/	/
	12	6	260	270	160	153	145
Oven	8	1	210	220	160	130	125
Oven Dimension (mm)		695*560*320					
Consumption		8.47m ³ /h	9.85m ³ /h	5.36kg/h			
Total power (kW)		12*6+8=80 (Natural Gas)					
Total power (kW)		10*6+8=68 (L. P. Gas)					
Ignition Way		Hot plates		Oven			
Manually		Piezo Igniter		Piezo Igniter			
Valve Types		Flame-out protection					
Temperature Control		Only the oven					
Temperature control range		100-300°C					

主要配件:

炉架搪瓷处理, 900为厚重型

炉头表面搪瓷处理

煲仔炉: A60旋塞阀-台湾达理 (熄火保护, 手动点火)

焗炉: 温控阀A65T-台湾达理 温控范围100-300°C

焗炉: 限温器-福兰德 350°C

焗炉: 压电陶瓷 (国内: 锐创) 自动点火

焗炉: 304不锈钢管 (中山: 凤升翔)

